

INSTRUMENT CHAMBER SELECTION GUIDE BAC 92 SERIES

Selection		Suffix Codes														Description			
A	Instrument Type	G																GWR	
		V																Vertical Level Switch	
		H																Horizontal Level Switch	
B	Mounting Style	SS																Side-Side	
		SB																Side-Bottom	
		XX																Special (Specify)	
C	Chamber Material	CS																A106 Gr. B	
		LF																A333	
		S2																SS-316 / 316 L	
		S8																Inconel 825	
		XX																Special (Specify)	
D	Instrument Chamber Size				2													2"	
					3													3"	
					4													4"	
					X														Special (Specify)
E	Instrument Chamber Pipe Schedule					A												Sch. 10	
						B												Sch. 40	
						C													Sch. 80
						D													Sch. 160
						X													Special (Specify)
F	Instrument Connection Size (Flanged)								2									2"	
									3									3"	
									4									4"	
									X										Special (Specify)
G	Instrument Connection Rating (Flanged)									A								150#	
											B							300#	
												C						600#	
												D							900#
												E							1500#
												F							2500#
												X							Special (Specify)
H	Instrument Connection Finish (Flanged)										RF							RF	
											WN							WNRF	
											SJ							SORTJ	
											WJ								WNRTJ
											XX								Special (Specify)
I	Chamber Bottom Style										D							Dished End	
											B							Bottom cover	
											X								Special
J	Process Connection Size																	1/2"	
																		3/4"	
																		1"	
																			1.5"
																			2"
																			2.5"
																			3"
																			4"
																			Special (Specify)
K	Process Connection Rating																	150#	
																		300#	
																		600#	
																		900#	
																			1500#
																			2500#
																			NPT(F) - 3000#
																			Special (Specify)
L	Process Connection Type																	Threaded	
																		RF	
																		WNRF	
																			SORTJ
																			WNRTJ
																			Special (Specify)

INSTRUMENT CHAMBER SELECTION GUIDE BAC 92 SERIES

Selection	Suffix Codes	Description
M	PL	Plugged
	FL	Flanged
	FV	Flanged with Valve
	SV	Screwed with Valve
	XX	Special
N	1	1/2"
	2	3/4"
	3	1"
	X	Special (Specify)
O	A	150#
	B	300#
	C	600#
	D	900#
	E	1500#
	F	2500#
	T	NPT(F) - 3000#
X	Special (Specify)	
P	TH	Threaded
	RF	RF
	WN	WNRF
	SJ	SORTJ
	WJ	WNRTJ
	XX	Special (Specify)
Q	PL	Plugged
	FL	Flanged
	FV	Flanged with Valve
	SV	Screwed with Valve
	XX	Special
R	1	1/2"
	2	3/4"
	3	1"
	X	Special (Specify)
S	A	150#
	B	300#
	C	600#
	D	900#
	E	1500#
	F	2500#
	T	NPT(F) - 3000#
X	Special (Specify)	
T	TH	Threaded
	RF	RF
	WN	WNRF
	SJ	SORTJ
	WJ	WNRTJ
XX	Special (Specify)	
U	OO	No Accessories
	SN	Studs & Nuts
	GS	Gasket Spiral Wound
	GF	Gasket Flat (Gra.)
	GX	Gasket Special
V	C to C or C to B Distance	XXXX Specify with unit

Note: Other information as per data sheet